



PIX - ULTRAFLEX® / K

STANDARDS: PIX PROPRIETARY. EN 857 2SC, SAE 100 R16S, ISO 11237-1 FOR REFERENCE



Application:

Medium to high pressure hydraulic lines. Suitable for petroleum based hydraulic fluids, synthetic esters, biodegradable hydraulic fluids, water-glycol based fluids and air.

Special Features:

Very good flexibility. Half bend radius than relevant standards EN 853 / EN 857/SAE 100R1S/SAE 100R2S/SAE100 R12. Very low MBR for short assembly length and very narrow installation.

Product Code	Dash DN	Hose ID (inch)	Hose ID (mm)	Braid OD (mm)	Hose OD (mm)	Maximum Working Pressure			Minimum Burst Pressure			Minimum Bend Radius (mm)	Weight/Meter (Kg/mtr)	Recommended Ferrule
						MPa	bar	psi	MPa	bar	psi			
UF206K	-4 6	1/4	6.4	11.4	13.5	40.0	400	5800	160.0	1600	23200	38	0.305	PF 22 06
UF208K	-5 8	5/16	7.9	13.0	15.0	35.0	350	5000	140.0	1400	20000	43	0.345	PF 22 08
UF210K	-6 10	3/8	9.5	15.1	17.1	33.0	330	4785	132.0	1320	19140	45	0.420	PF 22 10
UF212K	-8 12	1/2	12.7	18.3	20.5	27.5	275	3988	110.0	1100	15950	65	0.520	PF 22 12
UF216K	-10 16	5/8	15.9	21.5	23.5	25.0	250	3625	100.0	1000	14500	85	0.620	PF 22 16
UF219K	-12 19	3/4	19.0	25.5	27.5	21.5	215	3118	86.0	860	12470	100	0.855	PF 22 19
UF225K	-16 25	1	25.4	33.5	35.5	16.5	165	2393	66.0	660	9570	125	1.110	PF 22 25

Working Temperature: - 40°C to +100°C (Continuous)

Intermittent Temperature: - 40°C to +120°C (10% of total working hours)

Impulse Performance: 400000 cycles

Note: 1MPa = 10 bar = 145 psi

For air application (Temp. max 70°C) & pressure above 17 bar cover must be pin pricked. Special MSHA approved flame resistant outer cover can be provided on request.

** For Recommended Ferrule code please e-mail us at techsupport@pixtrans.com.