

TAPER BELTS V BELT PULLEYS

STANDARDS: SPA SECTIONS (067/1 - 106/6)



Part No	B	Z	Bush No	E	A Max	G	Pulley Type	D	H	C	Weight (KG)	F
SPA 067/1	67	1	1108	60	28	22				73.2	0.35	20
SPA 067/2	67	2	1108		28	22	6	13	37	73.2	0.47	35
SPA 071/1	71	1	1108	60	28	22	2			77.2	0.37	20
SPA 071/2	71	2	1108		28	22	6	13	40	77.2	0.54	35
SPA 071/3	71	3	1108		28	22	6	28	40	77.2	0.74	50
SPA 075/1	75	1	1108	60	28	22	2			81.2	0.44	20
SPA 075/2	75	2	1108		28	22	6	13	44	81.2	0.65	35
SPA 075/3	75	3	1108		28	22	6	28	44	81.2	0.84	50
SPA 080/1	80	1	1210	84	32	25	2			86.2	0.53	20
SPA 080/2	80	2	1210		32	25	6	10	50	86.2	0.62	35
SPA 080/3	80	3	1210		32	25	6	25	50	86.2	0.82	50
SPA 085/1	85	1	1210	88	32	25	2			91.2	0.68	20
SPA 085/2	85	2	1210		32	25	6	10	57	91.2	0.73	35
SPA 085/3	85	3	1210		32	25	6	25	55	91.2	0.96	50
SPA 090/1	90	1	1210	90	32	25	2			96.2	0.8	20
SPA 090/2	90	2	1610		42	25	6	10	60	96.2	0.8	35
SPA 090/3	90	3	1610		42	25	6	25	56	96.2	1.1	50
SPA 090/4	90	4	1615		42	38	6	27	56	96.2	1.4	65
SPA 090/5	90	5	1615		42	38	6	42	58	96.2	1.61	80
SPA 095/1	95	1	1210	90	32	25	2			101.2	0.9	20
SPA 095/2	95	2	1610		42	25	6	10	61	101.2	0.9	35
SPA 095/3	95	3	1610		42	25	6	25	61	101.2	1.3	50
SPA 095/4	95	4	1615		42	38	6	27	61	101.2	1.7	65
SPA 095/5	95	5	1615		42	38	6	42	63	101.2	1.83	80
SPA 100/1	100	1	1610	92	42	25	2			106.2	0.9	20
SPA 100/2	100	2	1610		42	25	6	10	66	106.2	1.1	35
SPA 100/3	100	3	1610		42	25	6	25	66	106.2	1.4	50
SPA 100/4	100	4	1615		42	38	6	27	66	106.2	1.9	65
SPA 100/5	100	5	1610		42	25	5	15	69	106.2	1.9	80
SPA 100/6	100	6	1610		42	25	5	30	69	106.2	2.23	95
SPA 106/1	106	1	1610	85	42	25	8	0	88	112.2	0.9	20
SPA 106/2	106	2	1610		42	25	6	10	72	112.2	1.3	35
SPA 106/3	106	3	1610		42	25	6	25	72	112.2	1.6	50
SPA 106/4	106	4	2012		50	32	6	33	72	112.2	1.7	65
SPA 106/5	106	5	2012		50	32	6	48	71	112.2	2.01	80
SPA 106/6	106	6	2012		50	32	6	63	71	112.2	2.53	95

Features :

- Produced to consistently high quality
- High wear resistance material for longer life
- Anodized finish to improve grip allowing increased power transmission
- Statically balanced to 40 mtr/sec (Q6.3 balance spec giving smoother vibration free running)



PIX Hydraulics Europe Limited

email: info@pixhose.com

- Consistent high quality, branded **POWERDRIVE** product