

**PIX-X'SET<sup>®</sup> MB**

**STANDARDS: BANDED BELTS**



Section	Dimensions		Angle (Deg)	Pitch (mm)	Standard	Recommended Minimum pulley diameter (mm)	Manufacturing Range		Length Designation
	Top width (mm)	Thickness (mm)					Min	Max	
HA	13.0	10.0	40	15.9	ISO 5291	80 de	33"	280"	Li
HB	17.0	13.0	40	19.0	ISO 5291	130 de	41"	628"	Li
HC	22.0	16.0	40	25.5	ISO 5291	210 de	46"	658"	Li
HD	32.0	21.5	40	37.0	ISO 5291	370 de	90"	658"	Li
HE	38.0	27.0	40	44.5	PIX	520 de	90"	658"	Li
HZ	10.0	8.5	40	10.3	PIX	55 de	45"	171"	Li
HSPZ	10.0	10.0	40	12.0	BS 3790	67 dp	1168 mm	9042 mm	Lp
HSPA	13.0	12.0	40	15.0	BS 3790	100 dp	914 mm	5000 mm	Lp
HSPB	17.0	16.0	40	19.0	BS 3790	160 dp	1778 mm	9144 mm	Lp
HSPC	22.0	20.0	40	25.5	BS 3790	224 dp	2235 mm	16688 mm	Lp
H3V	9.7	10.0	40	10.3	ISO 5290	67 de	35.5"	178"	La
H5V	15.8	16.0	40	17.5	ISO 5290	180 de	48"	660"	La
H8V	25.4	25.0	40	28.6	ISO 5290	317 de	98"	664"	La