

**PIX-X'TRA[®] VS
STANDARDS:**



| Section | Top width (Nominal) (mm) | Thickness (Nominal) (mm) | Angle (Deg) | Manufacturing Range | |
|---------------|--------------------------------|--------------------------------|----------------|------------------------|-------------|
| | | | | Pitch Length | |
| | | | | Min (mm) | Max (mm) |
| 22V-A22/1422V | 22 | 8 | 22 | 700 | 5115 |
| 30V-A22/1922V | 30 | 10 | 22 | 700 | 5125 |
| 37V-A22/2322V | 37 | 11 | 22 | 700 | 5126 |
| 30V-A26/1926V | 30 | 11 | 26 | 700 | 5126 |
| 46V-A26/2926V | 46 | 13 | 26 | 700 | 5137 |
| 51V-A26/3226V | 51 | 13 | 26 | 700 | 5137 |
| 40V-A30/2530V | 40 | 15 | 30 | 700 | 5146 |
| 51V-A30/3230V | 51 | 16 | 30 | 700 | 5147 |
| 70V-A30/4430V | 70 | 18 | 30 | 700 | 5157 |
| 64V-A36/4036V | 64 | 18 | 36 | 700 | 5157 |
| 70V-A36/4436V | 70 | 18 | 36 | 700 | 5157 |
| 76V-A36/4836V | 76 | 19 | 36 | 700 | 5161 |

Conforms to RMA IP 25/1991 Standards.